Full Colour Multi Function Printer

RICOH imagine. change.

RICOH IM C3000 / C3000LT IM C3500 / C3500LT IM C4500 / C4500LT IM C6000 / C6000LT



Welcome to a new era of technology that keeps your workplace up to date with RICOH IM C3000 / C3000LT / C3500 / C3500LT / C4500 / C4500LT / C6000 / C6000LT range of intelligent devices. Device and technology that is designed to grow and adapt, just as your business does.

Today's workplace needs to be ready for tomorrow. RICOH Intelligent Devices provide smooth access to functionality upgrades and productivity enhancements when they are released, without needing to change your hardware. Turn your device into a powerful hub that helps you manage information workflows efficiently, using technology that is scalable, secure, sustainable and simple.

Now is the time to:

- Protect your devices with easy access to security updates
- Take advantage of easy productivity upgrades at your own pace
- Save costs by bringing high-standard quality print output in-house
- Maximise productivity with streamlined workflows









Ricoh IM C4500Outstanding 45-ppm Colour Copier MFP

Excellent Performance with the Best Quality Output

Greater Control of Scan and Print Management

Scanning of smaller sized documents can be easily done with the new small sized paper scan unit. The double feed detection unit helps to improve scan accuracy while the EFI controller enhances print management. Now, you can also create professional grade flyers at your own convenience with our inner multi-folding unit.



Seamless User Experience

Our intelligent devices offer efficient working and reduced user intervention by expanding paper capacity. Choose from our versatile finishing and paper options for a professional touch to save time and reduce outsourcing expenses. With RICOH Intelligent Support, experience maximum device uptime and minimal disruption across all your devices.





Maximise Cost Savings

Enjoy lower running costs and reduced energy consumption thanks to environmentally friendly low TEC (Typical Electricity Consumption) values. Furthermore, take advantage of RICOH Intelligent Support services that anticipate potential issues and send corrective instructions via the Smart Operation Panel, avoiding interruptions and prolonging the optimal performance of your device – avoiding the need for intervention by more costly IT resources.



Next-level Productivity with Smart Operations

Interact with the 10.1" Smart Operation Panel like a typical smart device and configure it for quick and easy access to apps you use most often. A variety of mobile connectivity options enable printing or scanning to the office network or cloud from a smart device with built in support for NFC, AirPrint® or Mopria®. All this underpinned by a unique suite of support apps from RICOH Smart Integration.

RICOH IM C3000 / C3000LT / C3500 / C3500LT / C4500 / C4500LT / C6000 / C6000LT

MAIN SPECIFICATIONS

MODEL	RICOH IM C3000 / C3000LT	RICOH IM C3500 / C3500LT	RICOH IM C4500 / C4500LT	RICOH IM C6000 / C6000LT		
GENERAL	RICOTTINI COCCOT COCCOET	MCOTT IN C3300 / C3300Ei	111001111111111111111111111111111111111	MICOTI IIII COOOO / COOOOEI		
Warm-up Time	21 Seconds					
First Output Speed : B/W	4.5 Seconds			3.6 Seconds 2.9 Seconds		
First Output Speed : Full Color	6.9 Seconds	6.9 Seconds	5.4 Seconds	4.2 Seconds		
Continuous Output Speed	30ppm	35ppm	45ppm	60ppm		
Memory Std/Max	Зоррии			ооррии		
HDD Std/Max	2GB Std / 4GB Max					
ARDF Capacity		320GB Std/Max				
SPDF Capacity	100 Sheets 220 Sheets					
Weight [Mainframe]						
Dimensions W x D x H [Standard]	Less Than 85.5Kg Less Than 87.5Kg					
Dimensions W x D x H [Maximum]	587 x 685 x 788 mm					
(excluding ARDF/SPDF)	668 x 738 x 1030 mm					
Power Source		220 - 240V 50/60Hz				
COPIER						
Multiple Copying		Up to 99	9 Copies			
Resolution		600	dpi			
Zoom		From 25% to 4	00% in 1% Step			
PRINTER						
СРИ	Intel Atom Processor Ap	olloLake 1.3GHz / 1.1GHz	Intel Atom Processo	r ApolloLake 1.6GHz		
Printer Language : Standard		PCL5c, PCL6, Postscript 3 (emu	lation), PDF direct (emulation)			
Printer Language : Option	Genu	uine Adobe® Postscript®3™, XPS, IP	DS, PictBridge, PDF Direct from A	dobe®		
Print Resolution		1,200 x 1	,200 dpi			
Network Interface : Standard	Ethernet	t 10 base-T/100base-TX/1000 base-T	, USB Host I/F Type A, USB Device	I/F Type B		
Network Interface : Option	Bi-direction	onal IEEE 1284/ECP, Wireless LAN (II	EEE 802.11a/b/g/n), Additional NIC	(2nd port)		
Mobile Printing Capability		Apple AirPrint®, Mopria®, NFC,				
Windows® environments	Windows® 7, Windows®	8.1, Windows®10, Windows® Serve Windows®		Windows® Server 2012R2,		
Mac OS environments	Windows® Server 2016 Macintosh OS X10.11 or Later					
UNIX environments	UNIX	UNIX Sun® Solaris, HP-UX, SCO OpenServer, RedHat® Linux Enterprise, IBM® AIX				
	SAP® S/4®					
		SAP®				
SAP® environments Other Supported environments		SAP ^e IBM i	S/4®			
SAP® environments			S/4®			
SAP® environments Other Supported environments			S/4® Series			
SAP® environments Other Supported environments SCANNER		IBM i	S/4° Series / 240ipm (duplex)			
SAP® environments Other Supported environments SCANNER Scanning Speed		IBM i 120ipm (Simplex) 1,200 dpi (S/4° Series / 240ipm (duplex)			
SAP® environments Other Supported environments SCANNER Scanning Speed Resolution : Maximum		IBM i 120ipm (Simplex) 1,200 dpi (S/4® Series / 240ipm (duplex) via TWAIN) R, JBIG2), Grayscale compression PDF, Single page PDF			
SAP® environments Other Supported environments SCANNER Scanning Speed Resolution : Maximum Compression Method		IBM i 120ipm (Simplex) 1,200 dpi (TIFF (MH, MR, MM ingle page JPEG, Single Page High Multi page PDF, Multi page High c	S/4° Series / 240ipm (duplex) via TWAIN) R, JBIG2), Grayscale compression PDF, Single page PDF-A			
SAP® environments Other Supported environments SCANNER Scanning Speed Resolution : Maximum Compression Method File Formats		IBM i 120ipm (Simplex) 1,200 dpi (TIFF (MH, MR, MM ingle page JPEG, Single Page High	S/4° Series / 240ipm (duplex) via TWAIN) R, JBIG2), Grayscale compression PDF, Single page PDF-A			
SAP® environments Other Supported environments SCANNER Scanning Speed Resolution : Maximum Compression Method File Formats Scan Modes		IBM i 120ipm (Simplex) 1,200 dpi (TIFF (MH, MR, MM ingle page JPEG, Single Page High Multi page PDF, Multi page High c Email, Folder,	S/4° Series / 240ipm (duplex) via TWAIN) R, JBIG2), Grayscale compression PDF, Single page PDF-A			
SAP® environments Other Supported environments SCANNER Scanning Speed Resolution : Maximum Compression Method File Formats Scan Modes FACSIMILE		IBM i 120ipm (Simplex) 1,200 dpi (TIFF (MH, MR, MM ingle page JPEG, Single Page High Multi page PDF, Multi page High c Email, Folder,	Scries / 240ipm (duplex) via TWAIN) R, JBIG2), Grayscale compression PDF, Single page PDF- ompression PDF, Multi Page PDF- USB, SD Card			
SAP® environments Other Supported environments SCANNER Scanning Speed Resolution : Maximum Compression Method File Formats Scan Modes FACSIMILE Circuit		IBM i 120ipm (Simplex) 1,200 dpi (TIFF (MH, MR, MM ingle page JPEG, Single Page High Multi page PDF, Multi page High o Email, Folder, PSTN 2 Sec	Scries / 240ipm (duplex) via TWAIN) R, JBIG2), Grayscale compression PDF, Single page PDF-A USB, SD Card			
SAP® environments Other Supported environments SCANNER Scanning Speed Resolution : Maximum Compression Method File Formats Scan Modes FACSIMILE Circuit Transmission Speed		IBM i 120ipm (Simplex) 1,200 dpi (TIFF (MH, MR, MM ingle page JPEG, Single Page High Multi page PDF, Multi page High o Email, Folder, PSTN 2 Sec	S/4® Series / 240ipm (duplex) via TWAIN) R, JBIG2), Grayscale compression PDF, Single page PDF-A USB, SD Card , PBX onds			
SAP® environments Other Supported environments SCANNER Scanning Speed Resolution : Maximum Compression Method File Formats Scan Modes FACSIMILE Circuit Transmission Speed Modem Speed : Maximum		IBM i 120ipm (Simplex) 1,200 dpi (TIFF (MH, MR, MM ingle page JPEG, Single Page High Multi page PDF, Multi page High o Email, Folder, PSTN 2 Sec 33.6	S/4® Series / 240ipm (duplex) // 240ipm (dup			
SAP® environments Other Supported environments SCANNER Scanning Speed Resolution : Maximum Compression Method File Formats Scan Modes FACSIMILE Circuit Transmission Speed Modem Speed : Maximum Resolution : Standard		IBM i 120ipm (Simplex) 1,200 dpi (TIFF (MH, MR, MM ingle page JPEG, Single Page High Multi page PDF, Multi page High o Email, Folder, PSTN 2 Sec 33.6 8 x 3.65 line/mr	S/4® Series / 240ipm (duplex) via TWAIN) R, JBIG2), Grayscale compression PDF, Single page PDF-4 USB, SD Card , PBX onds Kbps n, 200 x 100 dpi			
SAP® environments Other Supported environments SCANNER Scanning Speed Resolution : Maximum Compression Method File Formats Scan Modes FACSIMILE Circuit Transmission Speed Modem Speed : Maximum Resolution : Standard Resolution : Option		120ipm (Simplex) 1,200 dpi (TIFF (MH, MR, MM ingle page JPEG, Single Page High Multi page PDF, Multi page High o Email, Folder, PSTN 2 Sec 33.6 8 x 3.65 line/m 16 x 15.4 line/m MH, MR, I	S/4® Series / 240ipm (duplex) via TWAIN) R, JBIG2), Grayscale compression PDF, Single page PDF-A USB, SD Card , PBX onds Kbps n, 200 x 100 dpi m, 400 x 400 dpi			
SAP® environments Other Supported environments SCANNER Scanning Speed Resolution : Maximum Compression Method File Formats Scan Modes FACSIMILE Circuit Transmission Speed Modem Speed : Maximum Resolution : Standard Resolution : Option Compression Method		120ipm (Simplex) 1,200 dpi (TIFF (MH, MR, MM ingle page JPEG, Single Page High Multi page PDF, Multi page High c Email, Folder, PSTN 2 Sec 33.6 8 x 3.65 line/mr 16 x 15.4 line/m MH, MR, I	S/4® Series / 240ipm (duplex) via TWAIN) R, JBIG2), Grayscale compression PDF, Single page PDF-4 USB, SD Card , PBX onds Kbps n, 200 x 100 dpi m, 400 x 400 dpi MMR, JBIG			
SAP® environments Other Supported environments SCANNER Scanning Speed Resolution : Maximum Compression Method File Formats Scan Modes FACSIMILE Circuit Transmission Speed Modem Speed : Maximum Resolution : Standard Resolution : Option Compression Method Memory : Standard		120ipm (Simplex) 1,200 dpi (TIFF (MH, MR, MM ingle page JPEG, Single Page High Multi page PDF, Multi page High c Email, Folder, PSTN 2 Sec 33.6 8 x 3.65 line/mr 16 x 15.4 line/m MH, MR, I	S/4® Series / 240ipm (duplex) via TWAIN) R, JBIG2), Grayscale compression PDF, Single page PDF-4 USB, SD Card , PBX onds Kbps n, 200 x 100 dpi m, 400 x 400 dpi MMR, JBIG 0 Pages)			
SAP® environments Other Supported environments SCANNER Scanning Speed Resolution : Maximum Compression Method File Formats Scan Modes FACSIMILE Circuit Transmission Speed Modem Speed : Maximum Resolution : Standard Resolution : Option Compression Method Memory : Standard Memory : Maximum		120ipm (Simplex) 1,200 dpi (TIFF (MH, MR, MM ingle page JPEG, Single Page High Multi page PDF, Multi page High c Email, Folder, PSTN 2 Sec 33.6 8 x 3.65 line/mr 16 x 15.4 line/m MH, MR, I 4MB (32 60MB (4,8)	S/4® Series / 240ipm (duplex) via TWAIN) R, JBIG2), Grayscale compression PDF, Single page PDF-4 USB, SD Card , PBX onds Kbps n, 200 x 100 dpi m, 400 x 400 dpi MMR, JBIG 0 Pages)			
SAP® environments Other Supported environments SCANNER Scanning Speed Resolution : Maximum Compression Method File Formats Scan Modes FACSIMILE Circuit Transmission Speed Modem Speed : Maximum Resolution : Standard Resolution : Option Compression Method Memory : Standard Memory : Maximum PAPER HANDLING		120ipm (Simplex) 1,200 dpi (TIFF (MH, MR, MM ingle page JPEG, Single Page High Multi page PDF, Multi page High of Email, Folder, PSTN 2 Sec 33.6 8 x 3.65 line/mr 16 x 15.4 line/m MH, MR, I 4MB (32 60MB (4,8	S/4® Series / 240ipm (duplex) via TWAIN) R, JBIG2), Grayscale compression PDF, Single page PDF-A USB, SD Card , PBX conds Kbps n, 200 x 100 dpi m, 400 x 400 dpi MMR, JBIG 0 Pages)			
SAP® environments Other Supported environments SCANNER Scanning Speed Resolution : Maximum Compression Method File Formats Scan Modes FACSIMILE Circuit Transmission Speed Modem Speed : Maximum Resolution : Standard Resolution : Option Compression Method Memory : Standard Memory : Maximum PAPER HANDLING Recommended Paper Size		120ipm (Simplex) 1,200 dpi (TIFF (MH, MR, MM ingle page JPEG, Single Page High Multi page PDF, Multi page High of Email, Folder, PSTN 2 Sec 33.6 8 x 3.65 line/mr 16 x 15.4 line/mr MH, MR, I 4MB (32 60MB (4,8) SRA3, A3, A4, A	Scries / 240ipm (duplex) // 240ipm (duplex)			
SAP® environments Other Supported environments SCANNER Scanning Speed Resolution : Maximum Compression Method File Formats Scan Modes FACSIMILE Circuit Transmission Speed Modem Speed : Maximum Resolution : Standard Resolution : Option Compression Method Memory : Standard Memory : Standard Memory : Maximum PAPER HANDLING Recommended Paper Size Paper Input Capacity Std		120ipm (Simplex) 1,200 dpi (TIFF (MH, MR, MM ingle page JPEG, Single Page High Multi page PDF, Multi page High of Email, Folder, 2 Sec 33.6 8 x 3.65 line/mr 16 x 15.4 line/m MH, MR, I 4MB (32 60MB (4,8 SRA3, A3, A4, A 1,200 4,700	Sories / 240ipm (duplex) // 240ipm (page PDF-A // 250ipm (page			
SAP® environments Other Supported environments SCANNER Scanning Speed Resolution : Maximum Compression Method File Formats Scan Modes FACSIMILE Circuit Transmission Speed Modem Speed : Maximum Resolution : Standard Resolution : Option Compression Method Memory : Standard Memory : Standard Memory : Maximum PAPER HANDLING Recommended Paper Size Paper Input Capacity Std Paper Input Capacity Max		120ipm (Simplex) 1,200 dpi (TIFF (MH, MR, MM ingle page JPEG, Single Page High Multi page PDF, Multi page High of Email, Folder, 2 Sec 33.6 8 x 3.65 line/mr 16 x 15.4 line/m MH, MR, I 4MB (32 60MB (4,8 SRA3, A3, A4, A 1,200 4,700	S/4® Series / 240ipm (duplex) // 240ipm (page PDF-4 // 250ipm (page P			
SAP® environments Other Supported environments SCANNER Scanning Speed Resolution: Maximum Compression Method File Formats Scan Modes FACSIMILE Circuit Transmission Speed Modem Speed: Maximum Resolution: Standard Resolution: Option Compression Method Memory: Standard Memory: Maximum PAPER HANDLING Recommended Paper Size Paper Input Capacity Std Paper Input Capacity Std		120ipm (Simplex) 1,200 dpi (TIFF (MH, MR, MM ingle page JPEG, Single Page High Multi page PDF, Multi page High of Email, Folder, PSTN 2 Sec 33.6 8 x 3.65 line/mr 16 x 15.4 line/m MH, MR, I 4MB (32 60MB (4,8) SRA3, A3, A4, A 1,200 4,700 500 S	S/4® Series / 240ipm (duplex) // 240ipm (page PDF-4 // 250ipm (page P			
SAP® environments Other Supported environments SCANNER Scanning Speed Resolution: Maximum Compression Method File Formats Scan Modes FACSIMILE Circuit Transmission Speed Modem Speed: Maximum Resolution: Standard Resolution: Option Compression Method Memory: Standard Memory: Maximum PAPER HANDLING Recommended Paper Size Paper Input Capacity Std Paper Output Capacity Max Paper Output Capacity Max	1,625	120ipm (Simplex) 1,200 dpi (TIFF (MH, MR, MM ingle page JPEG, Single Page High Multi page PDF, Multi page High of Email, Folder, 2 Sec 33.6 8 x 3.65 line/mr 16 x 15.4 line/m MH, MR, I 4MB (32 60MB (4,8) SRA3, A3, A4, A 1,200 4,700 500 S Sheets 60 - 30	S/4® Series / 240ipm (duplex) via TWAIN) R, JBIG2), Grayscale compression PDF, Single page PDF-A USB, SD Card , PBX onds Kbps n, 200 x 100 dpi m, 400 x 400 dpi MMR, JBIG 0 Pages) 00 Pages) 5, A6, B4, B5, B6 Sheets Sheets heets 3,625	Sheets		
SAP® environments Other Supported environments SCANNER Scanning Speed Resolution: Maximum Compression Method File Formats Scan Modes FACSIMILE Circuit Transmission Speed Modem Speed: Maximum Resolution: Standard Resolution: Option Compression Method Memory: Standard Memory: Standard Memory: Maximum PAPER HANDLING Recommended Paper Size Paper Input Capacity Std Paper Output Capacity Std Paper Output Capacity Max Paper Weight	1,625	120ipm (Simplex) 1,200 dpi (TIFF (MH, MR, MM ingle page JPEG, Single Page High Multi page PDF, Multi page High of Email, Folder, 2 Sec 33.6 8 x 3.65 line/mr 16 x 15.4 line/m MH, MR, I 4MB (32 60MB (4,8) SRA3, A3, A4, A 1,200 4,700 500 S Sheets 60 - 30	S/4® Series / 240ipm (duplex) via TWAIN) R, JBIG2), Grayscale compression PDF, Single page PDF-4 USB, SD Card , PBX onds Kbps n, 200 x 100 dpi m, 400 x 400 dpi MMR, JBIG 0 Pages) 00 Pages) 5, A6, B4, B5, B6 Sheets heets 3,625	Sheets		
SAP® environments Other Supported environments SCANNER Scanning Speed Resolution: Maximum Compression Method File Formats Scan Modes FACSIMILE Circuit Transmission Speed Modem Speed: Maximum Resolution: Standard Resolution: Option Compression Method Memory: Standard Memory: Maximum PAPER HANDLING Recommended Paper Size Paper Input Capacity Std Paper Output Capacity Std Paper Output Capacity Max Paper Weight Paper Types	1,625 Plain paper, Recycle	120ipm (Simplex) 1,200 dpi (TIFF (MH, MR, MM ingle page JPEG, Single Page High Multi page PDF, Multi page High of Email, Folder, 2 Sec 33.6 8 x 3.65 line/mr 16 x 15.4 line/m MH, MR, I 4MB (32 60MB (4,8) SRA3, A3, A4, A 1,200 4,700 500 S Sheets 60 - 30	S/4® Series / 240ipm (duplex) via TWAIN) R, JBIG2), Grayscale compression PDF, Single page PDF- ompression PDF, Multi Page PDF- USB, SD Card , PBX onds Kbps n, 200 x 100 dpi m, 400 x 400 dpi MMR, JBIG 0 Pages) 5, A6, B4, B5, B6 Sheets Sheets heets	Sheets		
SAP® environments Other Supported environments SCANNER Scanning Speed Resolution : Maximum Compression Method File Formats Scan Modes FACSIMILE Circuit Transmission Speed Modem Speed : Maximum Resolution : Standard Resolution : Option Compression Method Memory : Standard Memory : Maximum PAPER HANDLING Recommended Paper Size Paper Input Capacity Std Paper Output Capacity Std Paper Output Capacity Max Paper Weight Paper Types ECOLOGY	1,625 Plain paper, Recycle	120ipm (Simplex) 1,200 dpi (TIFF (MH, MR, MM ingle page JPEG, Single Page High Multi page PDF, Multi page High of Email, Folder, PSTN 2 Sec 33.6 8 x 3.65 line/mr 16 x 15.4 line/mr MH, MR, I 4MB (32 60MB (4,8) SRA3, A3, A4, A 1,200 4,700 500 S Sheets 60 - 30	S/4® Series 7 240ipm (duplex) via TWAIN) R, JBIG2), Grayscale compression PDF, Single page PDF-A USB, SD Card , PBX onds Kbps n, 200 x 100 dpi m, 400 x 400 dpi MMR, JBIG 0 Pages) 5, A6, B4, B5, B6 Sheets Sheets heets 1,625 100g/m² Letterhead, Cardstock, Preprinted oss paper, Label paper, OHP	Sheets d paper, Bond paper,		
SAP® environments Other Supported environments SCANNER Scanning Speed Resolution : Maximum Compression Method File Formats Scan Modes FACSIMILE Circuit Transmission Speed Modem Speed : Maximum Resolution : Standard Resolution : Option Compression Method Memory : Standard Memory : Maximum PAPER HANDLING Recommended Paper Size Paper Input Capacity Std Paper Output Capacity Std Paper Output Capacity Max Paper Weight Paper Types ECOLOGY Power Consumption : Max	1,625 Plain paper, Recycle Less That	120ipm (Simplex) 1,200 dpi (TIFF (MH, MR, MM ingle page JPEG, Single Page High Multi page PDF, Multi page High of Email, Folder, PSTN 2 Sec 33.6 8 x 3.65 line/mr 16 x 15.4 line/mr MH, MR, I 4MB (32 60MB (4,8) SRA3, A3, A4, A 1,200 4,700 500 S Sheets 60 - 30 e paper, Special paper, Color paper, Coated paper, Envelope, Gl	S/4® Series 7 240ipm (duplex) via TWAIN) R, JBIG2), Grayscale compression PDF, Single page PDF-0 mpression PDF, Multi Page PDF-0 USB, SD Card , PBX conds Kbps n, 200 x 100 dpi m, 400 x 400 dpi m/, 400 x 400	Sheets d paper, Bond paper,		

RICOH IM C3000 / C3000LT / C3500 / C3500LT / C4500 / C4500LT / C6000 / C6000LT


MAIN SPECIFICATIONS

MODEL	RICOH IM C3000 / C3000LT	RICOH IM C3500 / C3500LT	RICOH IM C4500 / C4500LT	RICOH IM C6000 / C6000LT			
INPUT / OUTPUT TRAY AND FINISHER OPTIONS							
1 x 550-Sheets Paper Tray (PB 3270)	Paper Size : A6-SRA3, Paper Weight : 60-300g/m²						
2 x 550-Sheets Paper Tray (PB 3280)	Paper Size : A6-SRA3, Paper Weight : 60-300g/m²						
2,000-Sheets Large Capacity Tray (LCIT PB3290)	Paper Size : A4, Paper Weight : 60-300g/m²						
1,500-Sheets Large Capacity Tray (LCIT RT3040)	Paper Size : A4, Paper Weight : 60-300g/m²						
1,000-Sheets Hybrid Finisher (SR3260)	Paper Size: Proof Tray: A6-A3, Shift Tray: A6-A3, Paper weight: 60-300g/m² Staple paper size: A4-A3, Staple paper weight: 52-105g/m Staple position: Top, Bottom, 2 Staples Staple capacity Max: 50 sheets (A4) 30 Sheets (A3) Stapleless capacity Max: 5 sheets (A4/A3)						
3,000-sheet Finisher (\$R 3280) [Available for IM C4500, IM C6000 only]	Paper Size : Proof Tray : A6-A3, Shift Tray : A6-A3, Paper weight : 60-300g/m² Staple paper size : A4-A3, Staple paper weight :52-105g/m Staple position : Top, Bottom, 2 Staples, Top slant Staple capacity Max : 50 sheets (A4) 30 Sheets (A3)						
1,000-Sheet Booklet Finisher (SR3270)	Paper Size: Proof Tray: A6-A3, Shift Tray: A6-A3, Booklet tray: A4-A3 Paper weight: 60-300g/m² Staple paper size: A4-A3, Staple paper weight: 52-105g/m Staple position: Top, Bottom, 2 Staples, Booklet Staple capacity Max: 50 sheets (A4) 30 Sheets (A3)						
2,000-Sheet Booklet Finisher (SR3290) [Available for IM C4500, IM C6000 only]	Paper Size: Proof Tray: A6-A3, Shift Tray: A6-A3, Booklet tray: A4-A3 Paper weight: 60-300g/m² Staple paper size: A4-A3, Staple paper weight: 52-105g/m Staple position: Top, Bottom, 2 Staples, Booklet Staple capacity Max: 50 sheets (A4) 30 Sheets (A3)						
500-Sheet Internal Finisher (SR3250) (IM C6000 is not supported)	Paper Size : A6-A3, Paper weight : 60-300g/m² Staple paper size : A4-A3, Staple paper weight :52-105g/m Staple position : Top, Bottom, 2 Staples Staple capacity Max : 50 sheets (A4) 30 Sheets (A3)						
250-Sheet Internal Finisher (SR3300) (Available for IM C3000, IM C3500 only)	Paper Size : A6-A3, Paper weight : 60-300g/m² Staple paper size : A4-A3, Staple paper weight :52-105g/m Staple position : Top,1 Staple Staple capacity Max : 2-5 sheets (A4)						
Internal Shift Tray (SH3080)	Tray Capacity: 250 sheets, Paper size: 320 mm x 600 mm or smaller, Paper weight: 60-300g/m ²						
One-bin tray (BN3130)	Tray Capacity : 125 sheets, Paper size : A5 - A3, Paper weight : 52-300g/m²						

OTHER OPTIONS

Platen Cover PN2000, DF3110, DF3120, Fax Option Type M37, G3 Interface Unit Type M37, Fax Connection unit Type M37, FAX Memory unit Type M19 64MB, Memory Unit Type M37 4GB, Caster Table Type M3, VM Card Type M37, Side Tray, Punch Unit NA/EU/SC (PU3070,PU3080,PU3090), Internal Multi-fold unit FD3010, Camera direct print card, Postscript3 Unit Type M37, XPS direct print Option Type M37, IEEE 1284 I/F Type M19, IEEE 802.11a/g/n I/F Type M19, Device server option Type M37, File format Converter Type M19, OCR Unit Type M13, Small Paper Feeding Unit Type M37, Page Keeper Type M37, ADF Handle, External Keyboard Bracket Type M19, Optional Counter Interface Unit Type M12, Key Counter Bracket Type M3, NFC Card Reader Type M37, Smart Card Reader Built in Unit Type M37, External USB Keyboard (No bracket), Color Controller E-25C, Unicode Font Package for SAP®License.





RICOH ASIA PACIFIC PTE LTD

30 Cecil Street, #13-01/08 Prudential Tower, Singapore 049712

Phone: +65 6830 5888, Fax: +65 6830 5830



















